





(317)346-4110

www.drainagesolutionsinc.com

**NOT FOR** CONSTRUCTION Copyright © Polymer Group Inc. All rights reserved Typar<sup>®</sup> is a registered trademark of Polymer Group Inc.

DISCLAMER:
THE INFORMATION CONTAINED IN THIS DETAIL IS PROVIDED FOR THE CONVENIENCE OF THE USER AND DOES NOT TAKE PLACE OF CONSTRUCTION PLANS ANDOR SPECIFICATIONS. POCYMER GROUP, INC. CAMMOTER EIGHT TAKE PLACE OF CONSTRUCTION PLANS ANDOR SPECIFICATIONS. POCYMER GROUP, INC. CAMMOTER EIGHT REPORT AND THE CONTROL FOR THE FIRST AND THE CONTROL FOR CONCEPT PURPOSES ONLY AND DOES NOT MAY YAMY ACTUAL DESIGN OR ENGINEERING HAS BEEN COMPLETED. ENGINEERING FOR CHIEF ONLY AND DOES NOT MAY YAMY ACTUAL DESIGN OR ENGINEERING HAS BEEN COMPLETED. ENGINEERING HOOLEN WILL INCED THE PERPORMED TO DETERMINE PROPER HYDROLOGICAL AND STRUCTURAL REQUIREMENTS AND COMPONENTS INCLUDING SAND AND AGGREGATE ALL MUTERIALS ARE BUSINETT ON AFFORMATION. BY POLYMER FOR MORPOR, BY CONCEPT, AND THE CONCEPT OF THE PROPERTY OF

## NOTES:

Note 1: Contact your utility company prior to trenching. Consult a professional arborist if root trimming is required.

Note 2: Install & Cover Biobarrier<sup>®</sup> as soon as possible (within 12 hours) after opening. High temperatures and direct sunlight can reduce

Note 2: Initials it Cover blockmer\*—as some as possible (within 12 hours) after opening. High temperatures and direct suringht can reduce effective product list.

If the product list is not a suring the product list is not a suring the product list.

If the product list is not a suring the product list is not sure and adjacent to protection area. 
Note 4: Initials 1797# Blockmeriff\* Root Control Fabric or the side of the tench opposite the root source. 
Note 5: Initials 1798# Blockmeriff\* Root Control Fabric or the side of the tench opposite the root source. 
Note 5: Initials 1798# Blockmeriff\* Root Control Fabric or the side of the tench opposite the root source. 
Note 6: Exinging should penetrate labric between the noclules 14 it. In non-loopedge of behic and at a 45\* angle to the trenchwall.

Specific advice on the use of Biobarrier® can be obtained from Polymer Group Inc.

Table 1 : Biobarrier® Specifications

Description	Da	ata		
Product Chemical Family	Biobarrier® Root Control System Thermoplastic Polyolefin			
	Polypropylene	> 74.8%		
Composition	UV Stabilizer	< 5%		
	Trifluralin	< 20%		
	PigmentMasterbatch <sup>1</sup>	< 0.5%		
Appearance Physical State Vapor Pressure* Bolling Point Solubility (H <sub>2</sub> O)* Vapor Density Packing Density Odor pt Packing Density Odor pt Pressure Control Benedit Gravity Percent Voisities UV realisatance Corroshity Filamability Toxidity Hygroscopicity Explosity Hygroscopicity Explosity Explosity Filamability	Gray Fabric Solid 13.7 mPa @ 25°C Not Applicable 0.2 ppm @ 25°C Not Applicable None None None			
Fabric				
Unit Weight Tensile Strength (ibs.) Elongation at Break (%) Mullen Burst Strength (psi) Puncture Strength (ibs.) Coefficient of Permeability (cm/sec.)	4.0 45.0 > 70.0 175.0 50.0 3 x 10 <sup>2</sup>			
Nodule				
Base Dlameter (in.) Height Weight (os.) Spacing (in.)	7/16 1/4 0.013 1-1/2			

Chart 1: Examples of Intended Biobarrier® Root Control Applications & Roll Widths

Application -	Root Control Width in. (cm)						
	12 (30)	19.5 (50)	24 (61)	29 (74)	39 (99)	58.5 (149	
Building Foundations					×	X	
Burial Vaults/Tombstones						×	
Containers			×	X	X	X.	
Curbs		×	×				
Drain Lines	X	×	X	×	X	X	
Earthdams						X	
Golf Greens/Tees/CartPaths		X	X	X	х	-	
Landfills						×	
Medians			X	X	X.		
Paths	X	X:	X	×	20,00		
Planting Beds		X	X	X	х	X	
Pot 'N' Pot	SOLD IN 6" X 12" SWATCHES (500/BOX)						
Pots	X	X:					
Retaining Walls				X	X	×	
Roads		X:	X	×	20,000		
Roof Gardens					X	X	
Septic Tanks/Fields						×	
Sidewalks		X:	×	X			
Swimming Pools		X.	×	X	X		
Tennis Courts		X	×	×	×		
Underground Pipes/Cables	X	X	X	X	X	X	
UndergroundStorage Tanks						X	
Utility Substations		X	X	X	X		

Chart 1 is a general guide only. Your specific applications may require slightly different sizes. As a general rule, the greater the fabric width, the greater the degree of protection against costly root damage. But, like any other root barrier the protection does not extend beyond the edge of fire fabric. So it is important to use adequate length and width to assure proper protection.

This field guide is provided as an aid to assessing root control in commonly encountered site conditions. Polymer Group Inc. accepts no responsibility for any loss or damage resulting from the use of thisguide.

Please note that the information above is given as a guide only. All sizes and weights are nominal figures and may vary to what is published. Polymer Group inc. cannot be liable for damage caused by incorrect insaliation of this product. Final determination of the suitability of any information or material for the use contemplated and the manner of its use is the sole responsibility of the user and the usermust assume all riskand responsibility in connection therewith.

Biobarrier® Root Control Fabric For Retaining Wall Applications

Specification, Design & Installation Guide