

# TANK ALERT® 4X ALARM SYSTEM

Easy to Install Liquid Level Alarm System with NEMA 4X Enclosure for Indoor or Outdoor Use

This alarm system monitors liquid levels in lift pump chambers, sump pump basins, holding tanks, sewage, agricultural, and other water applications.

The Tank Alert® 4X alarm system can serve as a high or low level alarm depending on the float switch model used.

The stainless steel alarm horn sounds and red LED beacon illuminates when a potentially threatening liquid level condition occurs. The horn can be silenced, but the alarm beacon remains on until the condition is remedied. Once the condition is cleared the alarm will automatically reset.

## FEATURES

- NEMA 4X enclosure rated for indoor or outdoor use
- Automatic alarm reset and alarm test/normal/silence switch
- Alarm horn sounds at 88 decibels at 10 feet (3 meters)
- Alarm system (when installed on separate circuit) operates even if the pump circuit fails

## OPTIONS

When ordered with the alarm, this system is available with:

- Alternate float switch models for high or low level warning
- Auxiliary dry contacts (normally open and normally closed) for easy attachment of remote devices



Indoor/Outdoor Alarms



(317) 346-4110  
[www.drainagesolutionsinc.com](http://www.drainagesolutionsinc.com)

**TANK ALERT® 4X** - Easy-to-install liquid level alarm system which has a NEMA 4X enclosure for indoor or outdoor use.

Part #	Description	Shipping Weight	List Price
1008024	4X-01HSGM (120 VAC w/15' SJE SignalMaster® High Level)	3.40 lbs.	\$502.00
1008026	4X-01LSGM (120 VAC w/15' SJE SignalMaster® Low Level)	3.40 lbs.	\$502.00
1008023	4X-01H (120 VAC w/15' Sensor Float® High Level)	3.65 lbs.	\$512.00
1008025	4X-01L (120 VAC w/15' Sensor Float® Low Level)	3.65 lbs.	\$512.00
1008027	4X-01X (120 VAC no float)	2.10 lbs.	\$447.00
OPTION AUX	Auxiliary alarm contacts (factory installed option only)	NA	\$28.00

H = High Level L = Low Level X = No Float **MASTER CARTON holds 12 boxed units.**

### CONTROL SWITCH OPTIONS

The Tank Alert® 4X alarm system comes standard with a 15 foot SJE SignalMaster® control switch with mounting clamp. Other float switches are available. See control switch section of the catalog. To determine the price of alarm with an alternate float, add the price of the part number with "no float" to the price of the float switch.

### SPECIFICATIONS

**VOLTAGE:** 120 VAC, 50/60 Hz

**ALARM ENCLOSURE:** 6.4 x 5.3 x 5 inches (16.2 x 13.5 x 13.34 cm),  
NEMA 4X, indoor-outdoor, weatherproof,  
UV stabilized thermoplastic

**ALARM HORN:** 88 decibels at 10 feet (3 meters)

**ALARM BEACON:** UL Listed, Type 4X beacon assembly

**AUXILIARY ALARM CONTACTS (OPTIONAL):** 120 VAC, 5 amps max.,  
50/60 HZ

**FLOAT SWITCH:** SJE SignalMaster® control switch with mounting clamp

**CABLE:** 15 feet (4.57 meters), flexible 18 gauge, 2 conductor (UL)  
SJOW, water-resistant (CPE)

**FLOAT:** 2.74 inch diameter x 4.83 inch long (7 cm x 12.3 cm), high  
impact, corrosion resistant polypropylene housing for use in  
sewage and non-potable water up to 140°F (60°C)

**MAXIMUM WATER DEPTH:** 30 feet (9 meters), 13 psi

**ELECTRICAL:** 5 amps, 125 VAC/250 VAC, 50/60 Hz



**DRAINAGE  
SOLUTIONS, INC**

(317) 346-4110

www.drainagesolutionsinc.com