






EROSION PROTECTION



FILTRATION



SEPARATION



DRAINAGE

## Mirafi® N-Series Nonwoven Polypropylene Geotextiles for Soil Separation and Drainage

TenCate develops and produces materials that function to increase performance, reduce costs and deliver measurable results by working with our customers to provide advanced solutions.

The Difference Mirafi® N-Series Nonwoven Geotextiles Make:


- **Construction.** Mirafi® N-Series polypropylene nonwoven geotextiles easily conform to the ground or trench surface for trouble free installation.
- **Strength.** Mirafi® N-Series geotextiles withstand installation stresses with high puncture and tear resistance.
- **Drainage.** High permittivity properties provide high water flow rates while providing excellent soil retention.
- **Environmental.** Mirafi® N-Series geotextiles are chemically stable in a wide range of aggressive environments.
- **Cost Effective.** Mirafi® N-Series geotextiles provide economical solutions to many civil engineering applications including a cost effective alternative to graded aggregate filters.

### APPLICATIONS

Mirafi® N-Series nonwoven geotextiles are used in a wide variety of applications including soil separation and drainage applications. Lightweight nonwovens are predominantly used for subsurface drainage applications along highways, within embankments, under airfields, and athletic fields. For these drainage structures to be effective, they must have a properly designed protective filter.

Mirafi® N-Series nonwoven geotextiles eliminates the challenge of determining the aggregate gradation required to match soil conditions, finding a convenient and economical source of a specific aggregate, transporting and placing graded aggregate, and assuring that the constructed in-place drainage system provides effective filter performance.

Heavyweight nonwovens are used in critical subsurface drainage systems, soil separation, permanent erosion control, and geomembrane liner protection within landfills. These geotextiles provide the required strength and abrasion resistance to withstand installation and application stresses to create an effective, long term drainage solution.



Mirafi® N-Series Nonwoven Geotextiles

### INSTALLATION GUIDELINES\*

French and Trench Drains Geosynthetic Placement

Cut geosynthetic to proper width prior to placement. Width should be enough to conform to the trench perimeter with at least a 6in (15cm) top overlap. Place the geosynthetic roll over the trench, and unroll enough geosynthetic that the geosynthetic can be placed down into the trench. Anchor the edges of the geosynthetic with heavy objects to prevent the geosynthetic from falling into the trench. Where overlaps are necessary between rolls, allow for 3 ft (.9m) overlap from the upstream to the downstream roll.

\* These guidelines serve as a general basis for installation. Detailed instructions are available from your TenCate representative.




# Mirafi® N-Series Nonwoven Polypropylene Geotextiles

## for Soil Separation and Drainage


MECHANICAL PROPERTIES	TEST METHOD	UNIT	140NL	140NC	140N	160N	170N	180N	1100N	1120N	1160N
Grab Tensile Strength:			<b>MINIMUM AVERAGE ROLL VALUE</b>								
Strength	ASTM D4632	lbs (N)	90 (401)	100 (445)	120 (534)	160 (712)	180 (801)	205 (912)	250 (1113)	300 (1335)	380 (1691)
Elongation	ASTM D4632	%	50	50	50	50	50	50	50	50	50
Trapezoid Tear Strength	ASTM D4533	lbs (N)	40 (178)	45 (200)	50 (223)	60 (267)	75 (334)	80 (356)	100 (445)	115 (512)	140 (623)
CBR Puncture Strength	ASTM D6241	lbs (N)	250 (1113)	250 (1113)	310 (1380)	410 (1825)	450 (2003)	500 (2224)	700 (3115)	800 (3560)	1025 (4561)
<b>HYDRAULIC PROPERTIES</b>											
Apparent Opening Size			<b>MAXIMUM OPENING SIZE</b>								
ASTM D4751	US Sieve (mm)		50 (0.30)	70 (0.212)	70 (0.212)	70 (0.212)	70 (0.212)	80 (0.18)	100 (0.15)	100 (0.15)	100 (0.15)
Permittivity			<b>MINIMUM ROLL VALUE</b>								
ASTM D4491	sec <sup>-1</sup>		2.0	2.0	1.7	1.5	1.4	1.4	0.8	0.8	0.7
Flow Rate			<b>MINIMUM TEST VALUE</b>								
ASTM D4491	gal/min/ft <sup>2</sup> (l/min/m <sup>2</sup> )		145 (5907)	140 (5704)	135 (5500)	110 (4481)	105 (4278)	95 (3870)	75 (3056)	65 (2648)	50 (2037)
UV Resistance After 500 hrs.			<b>MINIMUM TEST VALUE</b>								
ASTM D4355	% strength		70	70	70	70	70	70	70	70	70
<b>PACKAGING</b>											
Roll Width			12.5 (3.8)	12.5 (3.8)	12.5 (3.8)	12.5 (3.8)	12.5 (3.8)	12.5 (3.8)	15.0 (4.57)	15.0 (4.57)	15.0 (4.57)
			15.0 (4.57)	15.0 (4.57)	15.0 (4.57)	15.0 (4.57)	15.0 (4.57)	15.0 (4.57)			
Roll Length			360 (110)	360 (110)	360 (110)	300 (91.4)	300 (91.4)	360 (110)	300 (91.4)	300 (91.4)	150 (46)
			600 (502)	600 (502)	600 (502)	360 (110)	360 (110)	360 (110)	600 (502)	600 (502)	250 (209)
Roll Area			500 (418)	500 (418)	500 (418)	500 (418)	500 (418)	500 (418)	500 (418)	500 (418)	250 (209)
			600 (502)	600 (502)	600 (502)	600 (502)	600 (502)	600 (502)			

<sup>1</sup> Based on Third Party Testing Note: Values and methods could change without notice


### Mirafi® N-Series Woven Geotextiles



**Cut-off/Interceptor Drain Along a Roadway or Another Critical Structure**



**French Drain Without Pipe**



**Liner Protection Within a Landfill**

TenCate Geosynthetics Americas assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. TenCate Geosynthetics Americas disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

Mirafi® is a registered trademark of Nicolon Corporation.

© 2021 TenCate Geosynthetics North America

PDS.N0821

365 South Holland Drive  
Pendergrass, GA 30567

Tel +1 706 693 2226  
www.tencategeo.us

