

Biobarrier®: Drain Line Application



(317) 346-4110

DRAINAGE www.drainagesolutionsinc.com

Toll-Free: 1-800-541-5519

NOT FOR CONSTRUCTION

DISCLAIMER:
THE INFORMATION CONTAINED IN THIS DETAIL IS PROVIDED FOR THE CONVENIENCE OF THE USER AND DOES NOT TAKE PLACE OF CONSTRUCTION PLANS AND/OR SPECIFICATIONS, POLYMER GROUP, INC. CANNOT BE HELD RESPONSIBLE FOR THE USE OR MISUSE OF THIS INFORMATION, WE RECOMMEND YOU CONTACT US FOR PURTHER DESIGN ASSISTANCE.

DESIGN ASSISTANCE
INTIS DETAIL IS FOR CONCEPT PURPOSES ONLY AND DOES NOT MIPLY ANY ACTUAL DESIGN OR ENGINEERING HAS
BEEN COMPLETED. ENGINEERING MODELING WILL NEED TO BE PERFORMED TO DETERMINE PROPER
HYDROLOGICAL AND STRUCTURAL REQUIREMENTS AND COMPONENTS INCLUDING SAND AND AGGREGATE.
ALL MATERIALS ARE SUBJECT TO APPROVAL BY POLYMER GROUP, INC.

NOTES:

Note 1: Contact your utility company prior to trenching. Consult a professional arborist if root trimming is required.

Note 2: Install & Cover Biobarrier® as soon as possible (within 12 hours) after opening. High temperatures and direct sunlight can reduce effective product life.

Note 3: Dig trenches a minimum of 4 in. wide for Typar® Biobarrier® Root Control Fabric. Trenches must be a minimum length of mature plant canopy just(+) 10 ft. one entered on the root source and adjacent to protection area.

Note 4: Install Typar® Biobarrier® Root Control Fabric on the side of the trench opposite the root source.

Note 6: Install Typar® Biobarrier® Root Control Fabric with Nodules facing lowerd root source.

Note 6: Fixing pins should penetrate fabric between the nodules 1/4 in. from top edge of fabric and at a 45 ° angle to the trench wall.

Specific advice on the use of Biobarrier $^{\otimes}\,$ can be obtained from Polymer Group Inc.

Table 1 : Blobarrler® Specifications

Description		Data		
Product Chemical Family	Biobarrier [®] Root Control System Thermoplastic Polyolefin			
	Polypropylene	> 74.8%		
Composition	UV Stabilizer	< 5%		
	Trifluralin	< 20%		
	Pigment Masterbatch ¹	< 0.5%		
Appearance Physical State Vapor Pressure* Boiling Point Solubilly (H ₂ O)* Vapor Denaity Packing Density Odor pt Packing Density Odor pt Procession Rate Mething Palnt Specific Gravity Percent Volatiles UV realstance CorrosMty Flamabäty Toxicity Vigroscoplety Employabity Vigroscoplety EnglosAby EnglosAby	Gray Fabric Solid 13.7 mPa @ 25°C Not Applicable 0.2 ppm @ 25°C Not Applicable Not Note None None None None			
Fabric				
Unit Weight Tensille Strength (lbs.) Elongation at Break (%) Mullen Burst Strength (psi) Puncture Strength (lbs.) Coefficient of Permeability (cm/sec.)	4.0 45.0 > 70.0 175.0 50.0 3 x 10 ²			
Nodule				
Base Diameter (in.) Helght Welght (os.) Spacing (in.)	7/16 1/4 0.013 1-1/2			

Chart 1: Examples of Intended Blobarrier® Root Control Applications & Roll Widths

Application	Root Control Width In. (cm)							
	12 (30)	19.5 (50)	24 (61)	29 (74)	39 (99)	58.5 (149)		
Building Foundations					Х	X		
Burial Vaults/Tombstones						Х		
Containers			Х	Х	X	X		
Curbs		X	Х					
Drain Lines	X	X	X	X	X	X		
Earthdams						X		
Golf Greens/Tees/Cart Paths		X	X	X	X			
Landfills						X		
Medians			X	X	X			
Paths	X	X	X	X				
Planting Beds		X	X	X	X	X		
Pot 'N' Pot	SOLD IN 6" X 12" SWATCHES (500/BOX)							
Pots	X	X						
Retaining Walls				X	X	X		
Roads		X	X	X				
Roof Gardens					X	X		
Septic Tanks/Fields						X		
Sidewalks		X	X	X				
Swimming Pools		X	X	X	X			
Tennis Courts		X	Х	X	X			
Underground Pipes/Cables	X	X	X	X	X	X		
Underground Storage Tanks						X		
Utility Substations		X	X	X	X			
Blobarrier	® Root Control	is available in 20	ft. (6.1 m) or 10	0 ft. (30.5m) Rol	Lengths			

Chart 1 is a general guide only. Your specific applications may require slightly different sizes. As a general rule, the greater the fabric width, the greater the degree of protection against costly root damage. But, like any other root barrier the protection does not extend beyond the edge of the fabric. So it's important to use adequate length and width to assure proper protection

This field guide is provided as an aid to assessing root control in commonly encountered site conditions. Polymer Group Inc. accepts no responsibility for any loss or damage resulting from the use of this guide.

Please note that the information above is given as a guide only. All sizes and weights are nominal figures and may vary to what is published. Polymer Group inc. cannot be liable for damage caused by incorrect installation of this product. Final determination of the suitability of any information or material of the use contendated and the manner of its use is the sole responsibility of the user and the user must assume all risk and responsibility in connection therewith.

Biobarrier® Root Control Fabric For Utility & Pipe Applications