STANDARD ALARMS

For Sump, Sewage and Effluent



A Family and Employee Owned Company



SOLUTIONS, INC

(317)346-4110 www.drainagesolutionsinc.com

ALM-Series

- Indoor rated
- 115V Operation with 9-volt battery backup
- 86 Decibel horn
- Red LED alarm ring
- Green power "ON" light
- Auxiliary contacts
- Automatic alarm reset
- Alarm Test / Silence buttons
- 9-volt battery included

See ALM-EYE Series literature for Wi-Fi connected models



Patent: See LibertyPumps.com/patents

Super bright LED alarm ring

Models

ALM-2-1 Narrow angle float switch, 10' cord
ALM-2 Narrow angle float switch, 20' cord
ALM-P1 Compact snap-on float switch, 10' cord

ALM-PK Puddle sensor, 50' cord



Narrow Angle Float Switch (Sewage/Effluent application)



Compact Snap-on Float Switch Fits 1-1/4" or 1-1/2" pipe (Sump application)



Puddle Sensor (For floor level sensing)



ALM-2W & ALM-230W

Indoor/Outdoor ALM-2W - 115V ALM-230W - 230V

- Meets Enclosure Type 3R Standards
- 115V Operation, direct wire
- Thermoplastic enclosure
- Red alarm beacon
- 82 Decibel horn
- Alarm Test / Silence switch
- 20' Float switch cord
- Includes auxiliary contacts
- Easy field wiring with removable cover



ALM-3W

Commercial Outdoor

- NEMA 4X rated
- Commercial-duty enclosure
- 115V Operation, direct wire
- Flashing red alarm LEDs
- 95 Decibel horn
- Alarm "Test / ON / Silence" switch
- 20' Float switch cord
- Includes auxiliary contacts

