LCU-Series

Condensate Pumps



(317)346-4110

Shallow Tank

Height 1-3/4"

IAGE www.drainagesolutionsinc.com

For removal of condensate from high efficiency furnaces, A/C equipment, ice machines, drinking fountains, beverage machines, dehumidifiers, and other applications requiring condensate removal



LCU-SP Models

- Shallow Pan
- LCU-SP20S (115V) with safety switch
- LCU-SP220S (230V) with safety switch



LCU-15 Models

- LCU-15
- LCU-15T with tubing
- LCU-15S with safety switch
- LCU-15ST with safety switch and tubing





LCU-20 Models

- LCU-20S (115V) with safety switch
- LCU-20ST (115V) with safety switch and tubing
- LCU220S (230V) with safety switch
- LCU220ST (230V) with safety switch and tubing



LCU-Series

Features

- High impact ABS tank
- Wall mounts
- Three 1" intake holes
- 3/8" O.D. outlet
- Barbed and threaded discharge connection
- Removable check valve
- Stainless-steel shaft
- 6' Power cord with ground
- Thermally protected
- Fully automatic
- Quiet operation
- Models with an "S" include built-in safety switch
- Models with a "T" include 20' of tubing
- Isolation pads pre-installed on tank

Applications


- High efficiency furnaces
- AC equipment, ice machine
- Drinking fountains
- Dehumidifiers
- Other applications requiring condensate removal

Maximum fluid temperature: $150^{\circ}F$ ($65.5^{\circ}C$)



Performance Curve

60 Hz





Model LCU-15 (115V) Model LCU-15S (115V) Model LCU-15T (115V) Model LCU-15ST (115V)



Model LCU-20S (115V) Model LCU-20ST (115V) Model LCU220S (230V) Model LCU220ST (230V)



Shallow Pan Models: LCU-SP2OS (115V) LCU-SP22OS (230V)

Models

MODEL	HP	VOLTS	AMPS	HEIGHT	LENGTH	WIDTH	WEIGHT	CAPACITY	MAX HEAD	SAFETY SWITCH	20' TUBING
LCU-15	1/50	115	1	6.5"	11-1/8"	5"	4.5 lbs	2 US Qt	15'	No	No
LCU-15S	1/50	115	1	6.5"	11-1/8"	5"	4.5 lbs	2 US Qt	15'	Yes	No
LCU-15T	1/50	115	1	6.5"	11-1/8"	5"	5.5 lbs	2 US Qt	15'	No	Yes
LCU-15ST	1/50	115	1	6.5"	11-1/8"	5"	5.5 lbs	2 US Qt	15'	Yes	Yes
LCU-20S	1/30	115	1.5	6.5"	11-1/8"	5"	5.0 lbs	2 US Qt	20'	Yes	No
LCU-20ST	1/30	115	1.5	6.5"	11-1/8"	5"	6.0 lbs	2 US Qt	20'	Yes	Yes
LCU220S	1/30	230	0.7	6.5"	11-1/8"	5"	5.5 lbs	2 US Qt	20'	Yes	No
LCU220ST	1/30	230	0.7	6.5"	11-1/8"	5"	6.0 lbs	2 US Qt	20'	Yes	Yes
LCU-SP20S	1/30	115	1.5	5"	11-1/8"	5"	4.5 lbs	1 US Qt	20'	Yes	No
LCU-SP220S	1/30	230	0.7	5"	11-1/8"	5"	4.5 lbs	1 US Qt	20'	Yes	No