


6-Hole Distribution Box



Tough ProblemProviding a simple, reliable, and permanent means for dividing septic tank effluent flow.



TUF-TITE Solution

A strong, stable, permanent, non-corrosive Tuf-Tite Distribution Box, with a Tuf-Tite Speed Leveler in each outlet.

Tuf-Tite® Distribution Box. THE TOUGH ONE!

- **■** Injection molded HDPE
- Non-corrosive
- **■** Simple to install
- Easy to level

In a septic environment, no other material can match High Density Polyethylene in delivering a lifetime of trouble-free service. Tuf-Tite Distribution Boxes are injection molded, using only premium HDPE which contains no fillers or foam.



Snap-in pipe seals

They're patented. Simply insert your PVC pipe and push it through the flexible, polyethylene Tuf-Tite seal. Pipes fit watertight. Installation couldn't be easier.




They're permanent


Unlike cement-based pipe grout, Tuf-Tite seals will not crack or corrode in septic conditions. They stay pliable and watertight permanently.



6-Hole Distribution Box 6HD2



- HDPE is noncorrosive in a septic environment.
- Patented snapin pipe seals simplify installation.
- All Tuf-Tite products are U.V. stabilized.





Interlocking Lid. Heavy-duty HDPE Lid is ribbed for added strength and rigidity. Slotted sides interlock on the Distribution Box to assure a tight fit.

The 6HD2 Distribution Box comes complete with a Regular Lid or an Inspection Port Lid, and 8 snap-in fittings of your choice.

INSTALLATION IS JUST THIS SIMPLE

- Position the Distribution Box on level virgin soil.
 Do not place box on a concrete slab.
- 2. Install the inlet pipe and outlet pipes. Be sure the bottoms of all pipes rest on virgin soil.
- **3.** Level the Distribution Box and all pipes as needed.
- Backfill the pipes to within two feet of the Distribution Box. Recheck the level of the box, then backfill up to the top lid ridge.
- **5.** Install and adjust Tuf-Tite Speed Levelers.
- **6.** Place lid on the Distribution Box and finish backfilling.



Choice of Fittings

- S-35 Pipe Seal, for: Sewer and Drain
- Sewer and Drain

 SDR 35 ASTM 3034
- Thin Wall 1500 Lb. Crush
- P-10 Plug, for unused holes



Choice of Lids

Regular Lid. Molded of rugged HDPE.

Inspection Port Lid. For easy access and inspection. Accepts 4" riser pipes.



Tuf-Tite Speed Levelers™

Control the flow of effluent from the Distribution Box. Simply insert a Speed Leveler into each outlet pipe. Rotate each Speed Leveler so the flow is distributed as desired. Available for 3" or 4" PVC pipe.

