

The Company

Blocksom & Co. is a diversified manufacturer of a wide variety of natural fiber products. These products are marketed throughout the continental United States and Canada to supply the demands of industries including roofing, heating and air-conditioning, furniture, U.S. government and military, construction and aquaculture.

Our products are manufactured at company-owned facilities located in Michigan City, Indiana. We have been manufacturing and distributing quality natural fiber products continuously since 1919.



The Solution

Avoid clogged drains and expensive water damage by keeping leaves and large debris away from roof drains. Our economical, easy-to-install Roof Drain Filter holds drain-clogging litter, wind blown leaves and other debris away from the drain strainer but allows high water flow.

Roof Drain Filter installs in minutes, needs minimal upkeep and gives you the confidence that roof drains will keep flowing.

You'll appreciate the ease of installation using common hand tools, cable ties, roofing adhesive or wire. Easily maintain by sweeping top and sides to remove built up sediment and debris.

Millions of Homeowners Trust Us
to Filter the Air and Ventilate
Their Homes.

**You Can Trust Us to
Protect Your Roof Drains.**



**DRAINAGE
SOLUTIONS, INC**

Roof Drain Filter

(317) 346-4110

www.drainageproducts.us

Roof Drain Filter

Roof Drain Clogs?



Easy to install roof drain filter keeps debris away from drain to allow water to drain.



Features and Benefits:

- Keeps drains free of leaves and debris
- Porous texture allows high flow rate
- Exposed overflow reduces ponding
- 3 sizes in pads or rolls to fit any size drain
- Attaches to roof or strainer in minutes
- Easily maintain by sweeping top and sides to remove debris

Installation:



Tools for installation:

- utility knife/scissors
- needle nose pliers
- screwdriver
- tape measure

Choose a method of attachment:

Method 1: Cable Tie



Push a cable tie down through Filter Media an inch from center cut out. Bend tip of cable tie back on itself firmly and insert into strainer, loop around strainer fin and pull back out to attach. Needle nose pliers may be helpful to grab cable tie end to pull back through strainer. Pull zip ties snug to secure Filter to drain.

Ordering Information:




Strainer Diameter (up to)	Item #	Description	Pieces Per Carton	Cartons Per Pallet
15"	RD21R	21"x 21' roll	1 roll	16
15"	RD21P	21"x 21" pads	12 pads	16

Maintenance:



- Sweep top and sides of Roof Drain Filter to remove debris
- Remove debris from roof
- Check semi-annually and clean or replace



1. Remove sediment and debris around drain.



2. Verify size allows at least 3" of filter from outer edge of strainer.



3. To ensure a snug fit, cut two slits on net side to make an X-shaped opening the size of the strainer.




4. Slide Filter over strainer, net side down.

5. Trim off excess material around strainer.

Method 2: Metal Rod



Insert a 1/8" metal rod horizontally through Roof Drain Filter and strainer.



Method 3: Adhesive



Apply adhesive to secure Filter to roof. Use Roofing Cement on asphalt membrane. Use water-based adhesive to secure to synthetic roof membrane.



DRAINAGE
SOLUTIONS, INC.

(317) 346-4110

www.drainageproducts.us