

Biobarrier® : Retaining Wall Application



(317)346-4110 www.drainagesolutionsinc.com

> **NOT FOR** CONSTRUCTION Copyright © Polymer Group Inc. All rights reserved Typar[®] is a registered trademark of Polymer Group Inc.

Note 1: Contact your utility company prior to trenching. Consult a professional arborist if root trimming is required.

Note 2: Install & Cover Biobarrier[®] as soon as possible (within 12 hours) after opening. High temperatures and direct sunlight can reduce

Specific advice on the use of Biobarrier® can be obtained from Polymer Group Inc.

Table 1 : Biobarrier® Specifications

NOTES:

Description	Data			
Product Chemical Family	Biobarrier® Root ControlSystem Thermoplastic Polyolefin			
	Polypropylene	> 74.8%		
Composition	UV Stabilizer	< 5%		
	Trifluralin	< 20%		
	PigmentMasterbatch ¹	< 0.5%		
Appearance Physical State Vapor Pressure* Boiling Point Solubility (H ₂ O)* Vapor Density Packing Density Odor pt provision Rate Meeting Point Specific Gravity Percent Volatiles UV resistance Corrosivity Filamability Toddity Hygroscoplety Espolstrity Fight	Gray Fabric Solid 13.7 mPa @ 25°C Not Applicable 0.2 ppm @ 25°C Not Applicable No			
Fabric				
Unit Weight Tensile Strength (ibs.) Elongation at Break (%) Mullen Burst Strength (psi) Puncture Strength (psi) Coefficient of Permeability (cm/sec.)	4.0 45.0 570.0 175.0 50.0 3 x 10 ²			
Nodule				
Base Dlameter (in.) Height Weight (os.) Spacing (in.)	7/16 1/4 0.013 1-1/2			

Chart 1: Examples of Intended Biobarrier® Root Control Applications & Roll Widths

Application -	Root Control Width in. (cm)						
	12 (30)	19.5 (50)	24 (61)	29 (74)	39 (99)	58.5 (149	
Building Foundations					×	X	
Burial Vaults/Tombstones						×	
Containers			×	X	X	X.	
Curbs		X	×				
Drain Lines	X	X	X	X	X	X	
Earthdams						X	
Golf Greens/Tees/CartPaths		X	X	X	X		
Landfills						×	
Medians			X	X	X.		
Paths	X	X:	X	×	-20,000		
Planting Beds		X	X	X	X	X	
Pot 'N' Pot	SOLD IN 6" X 12" SWATCHES (500/BOX)						
Pots	X	X:					
Retaining Walls				X	X	×	
Roads		X:	X	×			
Roof Gardens					X	X	
Septic Tanks/Fields						×	
Sidewalks		X:	×	X			
Swimming Pools		- X	×	X	X		
Tennis Courts		X	×	×	X		
Underground Pipes/Cables	X	X	Х	X	X	X	
UndergroundStorage Tanks						X	
Utility Substations		X	X	X	X		

Chart 1 is a general guide only. Your specific applications may require slightly different sizes. As a general rule, the greater the fabric width, the greater the degree of protection against costly root damage. But, like any other root barrier the protection does not extend beyond the edge of fire fabric. So it is important to use adequate length and width to assure proper protection.

This field guide is provided as an aid to assessing root control in commonly encountered site conditions. Polymer Group Inc. accepts no responsibility for any loss or damage resulting from the use of thisguide.

Please note that the information above is given as a guide only. All sizes and weights are nominal figures and may vary to what is published. Polymer Group inc. cannot be liable for damage caused by incorrect insaliation of this product. Final determination of the suitability of any information or material for the use contemplated and the manner of its use is the sole responsibility of the user and the usermust assume all riskand responsibility in connection therewith.

Biobarrier® Root Control Fabric For Retaining Wall Applications

Specification, Design & Installation Guide