MODEL 404

"Short Profile" Drain Pump





(317)346-4110**DRAINAGE** www.drainagesolutionsinc.com

1/3 hp 3/8" Solids handling

Featuring QuickTree® technology for easy switch access!

Features

- Factory pre-assembled, ready to install
- Fully automatic operation
- Short profile design for compact areas - only 11" tall
- Separate access cover for easy switch inspection (QuickTree®)
- Integrally molded rubber gasket for a superior gas-tight seal
- Standard alarm and Wi-Fi alarmed models available

Applications

- Bar sinks
- Laundry trays
- Dehumidifiers
- Utility sinks
- Gray wastewater drainage below gravity lines









Model 404

Features

- Compact design for tight areas
- · Factory pre-assembled
- Fully automatic operation
- QuickTree® technology allows quick inspection and removal of float switch without disconnecting the plumbing
- Integrally molded rubber gaskets for a superior gas-tight seal
- Oil-filled, hermetically sealed motor with thermal-overload protection; 10', 3-wire power cord with grounded plug
- Corrosion-resistant polyolefin basin with molded-in connections
- Maintenance free, permanently lubricated sealed bearings
- 3/8" Solids handling

Maximum fluid temperature 104°F continuous duty, 140°F intermittent duty. Not intended for use with chemicals.

Motor Specifications

1/3 hp 115V 5.2A Oil-filled, Thermally protected


Dimensional Data

Weight: 13 lbs Height: 11-1/8" Major Width: 13-3/4"

Total Basin Capacity: 4.3 gallons

Performance Curve

60 Hz 3450 RPM



		DISCHADGE	STANDADD	Night Eve	CHECK VALVE
HP	VOLTS	INLET & VENT	ALARM	Wi-Fi ALARM	INCLUDED
1/3	115	1-1/2"			
1/3	115	1-1/2"			Χ
1/3	115	1-1/2"	Χ		
1/3	115	1-1/2"	X		Χ
1/3	115	1-1/2"		Χ	
1/3	115	1-1/2"		Χ	Χ
1/3	115	2"			
	1/3 1/3 1/3 1/3 1/3 1/3 1/3	1/3 115 1/3 115 1/3 115 1/3 115 1/3 115 1/3 115 1/3 115	1/3 115 1-1/2" 1/3 115 1-1/2" 1/3 115 1-1/2" 1/3 115 1-1/2" 1/3 115 1-1/2" 1/3 115 1-1/2" 1/3 115 1-1/2"	HP VOLTS INLET & VENT ALARM 1/3 115 1-1/2" 1/3 115 1-1/2" 1/3 115 1-1/2" 1/3 115 1-1/2" 1/3 115 1-1/2" 1/3 115 1-1/2"	HP VOLTS DISCHARGE INLET & VENT STANDARD ALARM Night Eye Wi-Fi ALARM 1/3 115 1-1/2" VIIII VI

Alarmed models come with factory mounted alarm float in system. No assembly required. See alarm literature for ALM Series standard alarm or NightEye[®] Wi-Fi alarm for complete alarm specifications.

404CV models are CSA certified to the UPC and IPC requirements of ASME A112.3.4 / CSA B45.9



QuickTree® technology allows easy removal of float switch without disconnecting plumbing or pulling the pump.

Heavy-duty integrally molded rubber gasket provides a superior seal. Meets 10' stack test requirements.