



**TANK ALERT® I** - Easy-to-install liquid level alarm system for indoor use.

Part #	Description (120V)	Shipping Weight	List Price
1007457	101-01H (120 VAC w/15' SJE SignalMaster® High Level)	3.58 lbs	\$204.00
1009207	101-01HSPKT (120 VAC w/15' SJE SignalMaster® High Level) with splice kit	3.58 lbs.	\$215.00
1003104	101-01H (120 VAC w/15' Sensor Float® High Level)	3.58 lbs.	\$216.00
1003365	101-01L (120 VAC w/15' Sensor Float® Low Level)	3.58 lbs.	\$216.00
1002235	101-01X (120 VAC no float)	2.14 lbs.	\$147.00
Part #	Description (230V)	Shipping Weight	List Price
1008009	101-02H (230 VAC w/15' SJE SignalMaster® High Level)	3.58 lbs.	\$284.00
1003364	101-02H (230 VAC w/15' Sensor Float® High Level)	3.58 lbs.	\$297.00
1005420	101-02L (230 VAC w/15' Sensor Float® Low Level)	3.58 lbs.	\$297.00
1005419	101-02X (230 VAC no float)	2.14 lbs.	\$228.00

H = High Level L = Low Level X = No Float SPKT = Splice Kit MASTER CARTON holds 16 boxed units.

**CONTROL SWITCH OPTIONS**

The Tank Alert® I alarm system comes standard with a 15 foot SJE SignalMaster® control switch with mounting clamp. Other float switches are available. See control switch section of the catalog. To determine the price of alarm with an alternate float, add the price of the part number with "no float" to the price of the float switch.

**SPECIFICATIONS**

**VOLTAGE FOR 120 VAC MODEL:**

**PRIMARY:** 120 VAC, 50/60 Hz, 5 watts max. (alarm condition)

**SECONDARY:** 12 VAC

**VOLTAGE FOR 230 VAC MODEL (not UL Listed or CSA Certified):**

**PRIMARY:** 230 VAC, 50/60 Hz, 5 watts max. (alarm condition)

**SECONDARY:** 12 VAC

**ALARM ENCLOSURE:** 6 x 4 x 2.5 inch (15.24 x 10.16 x 6.35 cm), NEMA 1 metal

**ALARM HORN:** 86 decibels at 10 feet (3 meters)

**POWER CORD:** 6 foot (1.8 meter)

**FLOAT SWITCH CONNECTION TERMINAL:** For float switch connection only. Do not apply power. (Voltage across terminals is 12 VAC.)

**FLOAT SWITCH:** SJE SignalMaster® control switch with mounting clamp

**CABLE:** 15 feet (4.57 meters), flexible 18 gauge, 2 conductor (UL) SJOW, water-resistant (CPE)

**FLOAT:** 2.74 inch diameter x 4.83 inch long (7 cm x 12.3 cm), high impact, corrosion resistant polypropylene housing for use in sewage and non-potable water up to 140°F (60°C)

**MAXIMUM WATER DEPTH:** 30 feet (9 meters), 13 psi

**ELECTRICAL:** 5 amps, 125 VAC/250 VAC, 50/60 Hz

Indoor Alarms



ESJOHFTPMVUJPOTJODDPN