Page 1/4

Revised On 01/04/2023

1 Identification of the substance and manufacturer		
Trade name: Product code: Recommended use: Uses advised against: Manufacturer/Supplier:	GOLF COURSE CLASSIC YELLOW 0000200696 Paint and coatings application. Any that differs from the recommended use. Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com	Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 www.seymourpaint.com
Emergency telephone number:	1-800-255-3924	
2 Hazard(s) identification Classification of the substance or r		
Flammable Aerosols 1 H222 Extremely flammable aerosol. Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated. Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation. Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation. Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure Additional information: GHS Hazard pictograms GHS02 GHS04 GHS07 GHS08		Route of exposure: Inhalation.
Signal word Hazard statements	Danger Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Suspected of causing cancer. Route of exposure: Inh May cause respiratory irritation. May cause damage to organs through prolonged or r	nalation.
Precautionary statements	Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surface Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even af Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. IF INHALED: Remove person to fresh air and keep of Call a poison center/doctor if you feel unwell. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures Dispose of contents/container in accordance with loc	es No smoking. ce. fter use. omfortable for breathing. s exceeding 50°C/122°F.

3 Composit	ion/information on ing	redients
Chemical o	haracterization: Mixtures	
Chemical E	Description:	This product is a mixture of the substances listed below with nonhazardous additions.
D		

Dangerous components:		
	Mineral Spirits	10-15%
	propane	10-15%
64742-89-8	VM&P Naphtha	5-10%
106-97-8		5-10%
	Isobutyl Acetate	5-10%
	Calcium Carbonate	5-10%
	Isopropyl Alcohol	1-5%
	titanium dioxide	1-5%
108-65-6	PM acetate	1-5%

4 First-aid measures	
After skin contact: After eye contact: After swallowing:	Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. Then consult a doctor. Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects: Indication of any immediate medical attention needed:	Dizziness No further relevant information available.

Revised On 01/04/2023

Trade name: GOLF COURSE CLASSIC YELLOW

5 Fire-fighting measures Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray. Special hazards: Can form explosive gas-air mixtures. Protective equipment for firefighters: A respiratory protective device may be necessary. 6 Accidental release measures Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol. Methods and material for containment and cleaning up: Ensure adequate ventilation. 7 Handling and storage Precautions for safe handling Use only in well ventilated areas. Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up. 8 Exposure controls/personal protection Components with limit values that require monitoring at the workplace: 74-98-6 propane PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) see Appendix F Minimal oxygen content (D, EX) 106-97-8 n-butane REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 1000 ppm (EX) 110-19-0 Isobutyl Acetate PEL (USA) Long-term value: 700 mg/m³, 150 ppm REL (USA) Long-term value: 700 mg/m³, 150 ppm TLV (USA) Short-term value: 150 ppm Long-term value: 50 ppm 67-63-0 Isopropyl Alcohol PEL (USA) Long-term value: 980 mg/m³, 400 ppm REL (USA) Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm Short-term value: 400 ppm TLV (USA) Long-term value: 200 ppm BEI, A4 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-63-0 Isopropyl Alcohol BEI (USA) 40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) Keep away from foodstuffs and animal feed. Wash hands after use. Hygienic protection: Wash hands after use. Do not eat or drink while working. **Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine. Nitrile gloves. Hand protection: The glove material must be impermeable and resistant to the substance. Eve protection: Tightly sealed goggles 9 Physical and chemical properties Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined. pH-value: Not determined (Contd. on page 3)

(Contd. of page 1)

Page 2/4

.

1

Revised On 01/04/2023

	Melting point/Melting range Boiling point:	Undetermined. -44 °C (-47.2 °F)	(Contd. of page 2)
	Flash point: Flammability (solid, gas):	-19 °C (-2.2 °F) Extremely flammable.	
	Decomposition temperature:	Not determined.	
	Auto igniting:	Product is not self-igniting.	
	Danger of explosion: Lower Explosion Limit: Upper Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. 0.5 Vol % 10.9 Vol %	
	Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octonal/water:	Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. Not determined.	
	Solubility: Viscosity: Water:	Not determined. Not determined. 17.1 %	
10	Stability and reactivity		
	Reactivity: Conditions to avoid:	Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in temperatures.	n subfreezing

Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information

LD/LC50 y	LD/LC50 values that are relevant for classification:		
	110-19-0 Isobutyl Acetate		
		4,763 mg/kg (rbt)	
67-63-0 ls			
Oral	LD50	4,570 mg/kg (rat)	
Dermal	LD50	13,400 mg/kg (rab)	
Inhalative	Inhalative LC50/4 h 30 mg/l (rat)		
13463-67-	7 titanium	l dioxide	
Oral	LD50	>20,000 mg/kg (rat)	
Dermal	LD50	>10,000 mg/kg (rbt)	
Inhalative	LC50/4 h	>6.82 mg/l (rat)	
108-65-6 F	108-65-6 PM acetate		
Oral	LD50	8,500 mg/kg (rat)	
Inhalative	LC50/4 h	35.7 mg/l (rat)	
Informatio	Information on toxicological effects: No data available.		
Skin effec	Skin effects: No irritant effect.		
Eye effect		No irritating effect.	
Sensitizat	Sensitization: No sensitizing effects known.		

12 Ecological information	
Aquatic toxicity: Persistence and degradability: Other information:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
Bioaccumulative potential: Mobility in soil: Other adverse effects:	No further relevant information available. No further relevant information available. No further relevant information available.

 13 Disposal considerations

 Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

 Recommendation:
 Completely empty cans should be recycled.

 Recommended cleansing agent:
 Water, if necessary with cleansing agents.

F

Trade name: GOLF COURSE CLASSIC YELLOW

(Contd. of page 3)

Revised On 01/04/2023

14 Transport information			
UN-Number DOT DOT ADR Transport hazard class(es): Class Marine pollutant: Special precautions for user: EMS Number: Packaging Group: UN "Model Regulation":	UN1950 UN1950 Aerosols, flammable 1950 Aerosols 2.1 Gases No Warning: Gases F-D,S-U UN1950, Aerosols, 2.1		
15 Regulatory information			
SARA Section 355 (extremely hazard	lous substances):		
None of the ingredients in this product			
SARA Section 313 (Specific toxic ch	emical listings):		
67-63-0 Isopropyl Alcohol			
Toxic Substances Control Act (TSCA): Canadian Domestic Substances List (DSL): Consumer Product Safety	All ingredients are listed or exempted.		
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.		
	California Proposition 65 chemicals known to cause cancer:		
	13463-67-7 titanium dioxide		
100-41-4 ethyl benzene			
Prop 65 chemicals known to cause birth defects or reproductive harm: None of the ingredients is listed.			
EPA:			
110-19-0 Isobutyl Acetate	D		
16 Other information			
Contact:	Regulatory Affairs		